

CSP-Nv Seismic Energy Source



Key features

- Microprocessor configuration and control.
- Intuitive user interface, with LCD display and LED indicators.
- Enhanced operator system feedback
- User programmable 'soft start'
- Master / Slave Key Support
- Additional safety/protection features
- Programmable voltage technology allows operator tuning to suit application
- All settings externally selectable
- High current and voltage solid state (semi-conductor) discharge method
- Debug log and diagnostics.
- Meets EC emissions regulations enabling interference-free field use
- Supplied in robust transit case, with HV junction box (HVJ3004) and mains lead.

CSP-Nv Overview

The CSP-Nv is built on the proven high voltage technology of the industry leading CSP range of power supplies. Incorporating microprocessor control and configuration for greater configuration flexibility and reliability whilst retaining a fail-safe logic design.

The CSP-Nv seismic energy source is the driving force behind Applied Acoustics' Dura-Spark range of sound sources that have extremely hard wearing electrode sparker tips.

The CSP-Nv adds to the standard safety systems and operational functions found across the entire range of CSP energy sources, the CSP-Nv is also suitable for use with the Applied Acoustics' S-Boom and single plate boomer systems.

Technical Specification

PHYSICAL

Size	Transit Case (7U) with cover in place and handles flat: 50cm(H) x 58cm(W) x 74cm(D)
Weight	CSP-Nv1200, case and cover: 61.5kg CSP-Nv2400, case and cover: 63.5kg

ELECTRICAL SPECIFICATION

Mains Input	240VAC 45-65Hz@ 5.0kVA single phase. 3 pin connector Variable Input Power Circuitry (AVIP) 'soft start' circuitry
Voltage Output	2500 to 3950VDC, 4 pin interlocked connector Solid state semi-conductor discharge method
Output Energy	Easy switch selectable in increments CSP-Nv1200: 50,100,150,200,250,300,350,400,450,500,550,600 700,800,900,1000,1100,1200 Joules CSP-Nv2400: 50,100,150,200,250,300,400,500,600,700,750,800, 900,1000,1250,1500,1750,2000,2250,2400 Joules
Charging Rate	2000J/second for continuous operation at 0-45°C
Capacitance	CSP-Nv1200 208µF, 108 shot life CSP-Nv2400 304µF, 108 shot life
Trigger	User configured: External: +ve key (5-12VDC), -ve key or isolated closure Internal: +ve key (5-12VDC), -ve key Opto isolated BNC connector on front panel and remote box (optional)
Repetition rate	User configured: External: 6pps maximum Internal: 166ms to 60 seconds Limited by charge rate, energy level and sound source rating
Earth	M8 stainless steel stud on front panel

SAFETY FEATURES

Features	Main microprocessor control circuits with fail-safe layer of logic circuitry LCD display with system status information, configuration Specially designed HV connector with interlock High speed dump resistors for high voltage components Capacitor bleed resistors HV output open circuit shutdown Trigger monitoring with time out and over clock shutdown HV output current monitor and shutdown Supply Voltage monitoring and shutdown High Voltage monitoring Over temperature shutdown Cover and connector interlocks Diagnostic log download for improved support Intelligent remote control available to configure, trigger and operate remotely
----------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

The unit's internal design has a modular construction for ease of servicing and capacitor replacement.
However, for safety reasons, only Applied Acoustics trained engineers should attempt a repair.

COMPATIBLE SOUND SOURCES

CSP-Nv1200	AA251/AA301 boomers and S-Boom triple plate; Dura-Spark L200, Dura-Spark UHD 240/400 and Dura-Spark 400+400.
CSP-Nv2400	AA251/AA301 boomers and S-Boom triple plate; Dura-Spark UHD 240/400 and Dura-Spark 400+400.