

Applied Acoustic Engineering Ltd Marine House, Marine Park, Gapton Hall Road, Great Yarmouth NR31 ONB, United Kingdom T +44 (0)1493 440355
E general@appliedacoustics.com
W appliedacoustics.com

2082 BluFin



Key features

- Bluetooth connectivity
- Ruggedised, light & compact design
- Easy configuration of 1100 and 1000 series acoustic positioning beacons
- Intuitive charging of applied acoustic positioning beacons, no setup required
- · Charge monitoring and diagnostic functionality
- Reduces setup time of equipment
- Bespoke design for offshore environments
- Long battery life

2082 BluFin Overview

The 2082 BluFin is a pocket-sized device with Bluetooth connectivity for the charging and configuration of 1100 and 1000 series Mini beacons.

Intuitive charging of applied acoustics positioning beacons, reducing equipment set-up time and user interaction prior to deployment via the BluFin mobile application.

Mechanical Specification:

Physical dimensions: 79mm x 57mm x 33mm

600mm MC-IL-5-F Pigtail

Environmental Specification:

IP66 rated housing

Storage -20° to 60°

Operation: 5°C to 40°C

Charge: 5°C to 30°C

Electrical Specification

Charging:	4-way charge Port, Power and Comms Interface lead supplied
DC input:	30V 1.5A, 2.1mm DC socket
Battery:	Internal 3.6V 150mA rechargeable NiMH
Operational Life:	6 hours* *Assuming constant pairing to a mobile device without connection to DC power
Standby life:	1 year
Charge Time:	30 hours (exhausted to full charge) ** **Unit can still be used while trickle charging

Bluetooth Specification

CERTIFIED TO FCC, ISED, CE, KCC, NCC AND SRRC

ISM Band:	2.402 to 2.480 GHz Operation
Channels:	0-39
RX Sensitivity:	-90 dBm
TX Power:	0 dBm
Range:	10m

User Interface

Hardware:	2 Tri-coloured LED's, Power / Reset button
Software:	BluFin Application Mobile [Android V10 or newer iOS 15 or newer/ Beacon Editor Application PC] [Windows 10 or Windows 11]
	Bluetooth: BLE V4.2 or later ***
	*** Earlier versions may not be compatible

Operation

Compatibility:	1000 and 1100 series beacons configuration
Charge Modes:	1000 and 1100 series beacons pre-charge, trickle charge, fast charge
Firmware:	Field upgradeable via App or PC interface

INCLUDED ACCESSORIES

30Vdc 40W PSU, Power and Coms Interface Lead, Mains Lead



APP STORE LINKS





Due to continual product improvement specification information may be subject to change without notice. 2082 BluFin/ Issue 1 August 2022

©aae technologies Ltd.